



## Declaration of Performance

Ref. number: VIAPANEL.VFP.D600.125.600.A.2

1. Unique identification code of the product-type:  
**VFP-A-D600-1000...6000x600x125 mm**
2. Intended use: In internal non-load-bearing partition walls of buildings
3. Manufacturer: Innoscitech Kft., H-4110 Biharkeresztes, külterület hrsz. 0166/64.  
E-mail: info@innoscitech.hu
4. Place of manufacture: H-4110 Biharkeresztes, külterület hrsz. 0166/64.
5. AVCP system: 4
6. Harmonised standard: MSZ EN 12602:2017

### 7. Declared performance

| Essential characteristics                                           |                                     | Performance                                     |
|---------------------------------------------------------------------|-------------------------------------|-------------------------------------------------|
| Product type                                                        |                                     | W7 (non-load-bearing wall component (vertical)) |
| Dimensions/<br>Tolerances                                           | Length [mm]                         | 1000 - 6000 $\pm$ 3                             |
|                                                                     | Thickness [mm]                      | 125 $\pm$ 1                                     |
|                                                                     | Width [mm]                          | 600 $\pm$ 1,5                                   |
|                                                                     | Deviation from squareness [mm/0.5m] | $\leq$ 0,2                                      |
| Dimensional tolerances                                              |                                     | T2                                              |
| Dimensional stability (shrinkage) (ecs,ref) [mm/m] / class          |                                     | $\leq$ 0,2 / 0,20                               |
| Compressive strength $f_{ck}$ [N/mm <sup>2</sup> ] / strenght class |                                     | $\geq$ 5,1 / AAC 5                              |
| Flexural strength [N/mm <sup>2</sup> ]                              |                                     | NPD*                                            |
| Gross dry density, average ( $\rho$ ) [kg/m <sup>3</sup> ]          |                                     | 600 $\pm$ 45                                    |
| Reaction to fire (Euroclass)                                        |                                     | A1                                              |
| Resistance to fire                                                  |                                     | EI 180 **                                       |
| Direct airborne sound insulation $R_w(C;Ctr)$ [dB]                  |                                     | NPD*                                            |
| Durability (freeze-thaw-resistance) EN 15304 [cycles]               |                                     | 100                                             |
| Mass loss ( $m_L$ ) [%]                                             |                                     | $\leq$ 5                                        |
| Decrease in compressive strength ( $f_{c,rel}$ ) [%]                |                                     | $\leq$ 15                                       |
| Shape                                                               |                                     | Rectangular-based straight prism                |
| Water vapour diffusion coefficient ( $\mu$ )                        |                                     | 5/10 (Tabulated value according to EN 1745)     |
| Thermal conductivity $\lambda_{10, DRY}$ (P= 50%) [W/(m·K)]         |                                     | 0,170 (Tabulated value according to EN 1745)    |
| Dangerous substances                                                |                                     | NPD*                                            |

\* NPD - no performance declared

\*\* Provided that the installation conditions comply with the relevant fire protection regulations and standards.

8. The performance of the product identified above is in conformity with the declared performance.  
This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.  
Signed for and on behalf of the manufacturer:

Biharkeresztes, 2026.07.06.

INNOSCITECH KFT.  
4110 Biharkeresztes  
külterület 0166/64 hrsz.  
Cégjegyzékszám: 09-09-036292  
Adószám: 23321489-2-09  
3

Simon Levente Direktor CEO.